



STUD WELDING PRODUCTS, INC

Your Number One Stud

STUD WELDING UNIT Model: StudPro 2500Xi

Made in USA 

| FEATURES | StudPro 2500Xi |
|---------------------|---|
| WELD RANGE | 14ga - 1/4" |
| DUTY CYCLE | 14 studs/minute (5/16" settings) |
| CAPACITANCE | 76,000 |
| WELD ENERGY | 1520 watts-second |
| PRIMARY POWER | 110 VAC @ 50/60 HZ 15 AMP 220 VAC @ 50/60 HZ 7.5 AMP |
| CHARGE VOLTAGE | 35-200 VDC |
| SIZE | 14" L X 10.5"W X 11.5"H |
| POWER UNIT WEIGHT | 18 LBS |
| GUN CABLE LENGTH | #4 x 25' |
| GROUND CABLE LENGTH | #4 x 15' |



FEATURES

- **NEW FEATURE** Intuitive Touchscreen Interface with Preset values for fast, accurate, and repeatable weld settings
- **NEW FEATURE** Set-Point Discharge: Unit discharges directly to a new set point without needing to discharge completely
- **NEW FEATURE** Universal Input Voltage: Plug and play, no need to re-tap the machine for 110V or 220V input voltages
- **NEW FEATURE** Low input voltage capability enables operation with long extension cords
- **NEW FEATURE** Contact and Trigger Indicators for fast troubleshooting of hand tool and weld cable maintenance issues
- **NEW FEATURE** Thermal and Voltage protection indicators to protect the unit from damage due to overheating
- Rigid internal construction minimizes the possibility of components coming loose during rough handling or operations
- Sheet metal is powder-coated for greater durability, texture, and appearance.
- Hand tool has an adjustable internal spring to apply the correct spring pressure for every welding application
- Hand tool can be configured for "B" collets, "CI" collets, Euro collets, or standard tapered chucks.

Visit our website at www.StudWeldProd.com or email Info@StudWeldProd.com

Downey, CA

9459 Washburn Rd
Downey CA 90242
Ph: 800-252-1919
Fax: 562-862-3022

Hayward, CA

2391 American Ave
Hayward, CA 94545
Ph: 510-782-7883
Fax: 510-782-7918

Renton, WA

927 Thomas Ave SW
Renton, WA 98057
Ph: 425-656-9787
Fax: 425-656-9786

Phoenix, AZ

3535 E Wier Ave #4
Phoenix, AZ 85040
Ph: 602-305-9350
Fax: 602-305-4890